

# DUAL SLIDING CONTAINMENT DOORS



## KEY FEATURES//

- > STANDARD & CUSTOM SIZES
- > RIGID DESIGN
- > CLEAR PANELS
- > NO THRESHOLD
- > SMOOTH ACTUATION
- > SELF SUPPORTING

## PRODUCT SPECS

## OVERVIEW

The Dual Sliding Door is an ideal solution to end-of-row hot or cold aisle containment in any data center. Doors are available in standard sizes for 42u to 51u cabinet mounting as well as custom sizes to fit under overhead obstructions or other sizing requirements. A self closing mechanism is included as standard on all doors together with the ability to 'hold open' doors for unimpeded access to the aisle. There are no obstructions on the floor of the aisle that could impede access of a person or cart.

DOORS & FRAME - Black, White or Anodized		
PHYSICAL PROPERTIES		
Property:	Material:	Result:
Tensile Strength	Aluminum	22,000 psi

PANEL INSERTS - ACRYLIC		
3MM – Acrylic		
FLAMMABILITY		
Property:	Test:	Result:
Smoke Dev.	ASTM E84	550
Flame Spread	ASTM E84	115
Horizontal Burn	ASTM D635	1.5 in/min
UL Horizontal	UL94	94 HB

PANEL INSERTS - Polycarbonate Twinwall		
6MM – polycarbonate		
Property:	Test:	Result:
Smoke Dev.	ASTM E84-08	100
Flame Spread	ASTM E84-08	10
R-Value	-	1.6

ABS PANEL INSERTS - Black or Clear		
PHYSICAL PROPERTIES		
Property:	Test:	Result:
Tensile Strength	ASTM D-638	5,400 psi



Corporate Office:  
200 Finn Court  
Farmingdale NY, 11735

East Coast: 631-249-9441  
West Coast: 650-429-8719  
Email: sales@afcosystems.com  
Web: www.afcosystems.com

All information is subject to change without notice.  
The information contained in this Product Data Sheet is the sole property of AFCO Systems. © 2014 AFCO Systems Inc. All rights reserved.